

SUSPENDED SOLIDS SENSOR



MULTI

- Flexible – choice of portable or stationary central units
- High quality stainless steel execution
- Flexible – choice of optical or electrochemical electrodes
- Long term stability and long maintenance intervals

SOLIDO

The Solido is a portable optical suspended solids meter using light transmission, which is the most accurate measuring principle for SS. Solido is designed to measure suspended solids in aeration basins, RAS, aerobic digesters in water and wastewater plants, as well as in other facilities. Two different alarm levels for the suspended solids

may be set to indicate high and low levels. It is able to store up to 250 measurements with information about time, date and location, that may be named by the user. Each location contains the suspended solids level and temperature that applied for the specific measurement sample.

TECHNICAL SPECIFICATIONS

Function	Suspended solids
Measuring principle	Optical light transmission
Wave length	NIR 850 nm
Measuring range	Up to 35000 mg/l (ppm) dependent on solids type
Accuracy suspended solids	1% FS (full scale)
Repeatability	< 2% of Measured Value
Type of Measurement	Continuous
Measuring units	g/l, mg/l, %, ppm
Maximum depth	19 m (62 ft)
Signal at Preset Alarm Values	Acoustic, Vibration, Display
Temperature Range - Liquid	0 – +50°C (+32 - 122°F)
Sensor Body	Stainless Steel, BK7 Glass Windows
Cable	PUR, Shielded
Cable Fitting	MatchClamp™
Weight Sensor	450g (1 lb)
Dimensions Sensor Body	145 mm x 32 mm Ø (5.7"x1.26"Ø)
Cable Length	4 m (13'), 8 m (26 ft), 12 m(36 ft)
Enclosure Sensor Body	IP68 (NEMA 7)

MULTI-SERIES

Solido is one of the sensors in the Multi-series. Please note that this is a new range of sensors and central units which are not compatible with the classic X-range of Cerlic sensors. The Multi-series also includes sen-

sors for sludge blanket and dissolved oxygen. There are both a portable and a stationary central unit to choose from. The Multi-series is flexible and cost effective.



CERLIC CONTROLS AB

P.O. Box 5084, SE-141 05 Kungens Kurva, Sweden • Tel: +46 8 501 694 00 • Fax +46 8 501 694 29
info@cerlic.se • www.cerlic.com